




# SNZ2-TZB Cross Recessed Micro Pan Head Screws - Type 0 - 2

Miniature Size



## Material/Finish



|           | SNZ2-TZB                              |
|-----------|---------------------------------------|
| Main Body | Steel<br>Trivalent Chromate Treatment |



- Miniature screws for precision instruments (No. 0 Class 2).
- M1.4 - M2.6.
- Pan head machine screw type with low head height. For applications with limited overhead space.

## Application

For making devices and equipment more compact  
Compact precision equipment

Unit : mm

| Part Number   | M (Coarse)        |       | L   |     |     |     |     |   |   |    |     |     | D <sub>1</sub> | L <sub>1</sub> | Cross-recessed Socket No. | Max. Tightening Torque (N · m) | Mass (g)    | Qty per Pack |
|---------------|-------------------|-------|-----|-----|-----|-----|-----|---|---|----|-----|-----|----------------|----------------|---------------------------|--------------------------------|-------------|--------------|
|               | Nominal of Thread | Pitch |     |     |     |     |     |   |   |    |     |     |                |                |                           |                                |             |              |
| SNZ2-M1.4-TZB | M1.4              | 0.3   | 2   | 3   | 3.5 | 4   | 5   | 6 | 8 | 10 | 2.5 | 0.5 | 0              | 0.07           | 0.03 - 0.1                | 50                             |             |              |
| SNZ2-M1.6-TZB | M1.6              | 0.35  | 2   | 2.5 | 3   | 3.5 | 4   | 5 | 6 | 8  | 10  | 2.8 | 0.55           | 0              | 0.11                      | 0.04 - 0.12                    | 50          |              |
| SNZ2-M1.7-TZB | M1.7              | 0.35  | 2   | 2.5 | 3   |     | 4   | 5 | 6 | 8  | 10  | 3.0 | 0.5            | 0              | 0.14                      | 0.05 - 0.14                    | 50          |              |
| SNZ2-M2-TZB   | M2                | 0.4   | 1.5 | 2   | 2.5 | 3   | 3.5 | 4 | 5 | 6  | 8   | 10  | 3.5            | 0.6            | 0                         | 0.22                           | 0.06 - 0.21 | 50           |
| SNZ2-M2.5-TZB | M2.5              | 0.45  |     |     | 3   |     | 4   | 5 | 6 | 8  |     | 4.3 | 0.9            | 0              | 0.46                      | 0.16 - 0.3                     | 50          |              |
| SNZ2-M2.6-TZB | M2.6              | 0.45  |     | 2.5 | 3   | 3.5 | 4   | 5 | 6 | 8  | 10  | 4.5 | 0.8            | 0              | 0.53                      | 0.16 - 0.39                    | 50          |              |

- When purchasing less volume than one full bag, a separate handling fee is charged. For details, see the Sold Separately Service.

## Part Number Specification

**SNZ2-M2-3-TZB**



|                          |                            |                         |                          |                                      |
|--------------------------|----------------------------|-------------------------|--------------------------|--------------------------------------|
| 1 Individual Sales       | Cleanroom Wash & Packaging | Screw Length Adjustment | Vibration Resistant      | Modification process for captive use |
| Available / Add'l charge | Available / Add'l charge   | Not Available           | Available / Add'l charge | Not Available                        |