Screw Length Adjustment Service

Service description

- Screws can be cut to your desired length in units of 1 mm.
- Example: When a **SVSS-M6-20** screw is cut by 2 mm.

Screw Length Adjustment

Screw

Length

18 mm

Processing

Length 2 mm

Standard Product

SVSS-M6-20 Screw Length 20 mm.





Applicable Products

• At the bottom of the product page, Available / Add'l charge message is indicated.

Ventilation Hole	Gas trappeo at the bottom of a screw hole Gas trapped in a drilled hole	SWAS-VF Washers	with Ventil
1 Individual Sales → P.xxxx	Scleanroom Wash & Packaging => P.xxxx	(🖬 í 🖬 Screw Length Adjustment 🔿 Puppor	💶 Vibratio
Available / Add'l charge	Cleanroom washed and packed	Available / Add'l charge	Not Availa
NBK	▶ +81-575-23-1162	▶info@nbk1560.com	<u>We</u>

• Applicable Screw Threads: M2 - M12



SVSS-M6-20-CT2 Cutting the 20 mm screw length by 2 mm to 18 mm.

 Specify the processing length in units of 1 mm.

- After processing a screw that had surface treatment, the screw tip is coated with lacquer.
- The minimum screw length is the thread diameter plus 2 mm.
 Example: For M8, the minimum screw length is 10 mm..
- The tolerance is ± 0.5 mm.
- The screw tip is a flat tip.

Fees • Delivery

• Please feel free to contact us.

Part number specification

SSH-M5-12-	-CT1
	Processing

Part Number

Processing Symbol Length

Specify the part number of the product to apply screw length adjustment, as well as the processing length (in units of 1 mm).