

















I Init : mm

## Material/Finish



- **SVFSS** Main Body SUSXM7 (Equivalent to SUS304) Strength Class A2-70
- Because the bearing surface is larger due to the head part flange, the pressure on the fastened material is dispersed compared to normal hex socket head cap screws, making bearing surfaces less likely to sink. Also, the bearing surface can be ensured even with large drilled hole diameters.
- Washer mounting work is not required, reducing the parts needed.
- Washerless design makes it ideal for automated screw fastening by robots.
- The ventilation hole easily releases gas trapped in the screw holes of equipment and machines, and supports vacuum drawing of vacuum devices.
- Cleanroom washing/cleanroom packing provided.
- For parts embedded in FPD production equipment, semiconductor manufacturing equipment, or food machinery, or used in cleanrooms.
- Application

FPD production equipment / Semiconductor manufacturing equipment / Food machinery

Part Number	M (Coarse)			142							D.	Do		L2*1	В		٠.	d may	Mass (g)		Ohu man Daak
	Nominal of Thread	Pitch	L <b>1</b> 2								D1	D <sub>2</sub>	L1	L2* 1	В	L	t1	u max.	Mass (g)		Qty per Pack
SVFSS-M4	M4	0.7	6	8	10	12	16	20			9	7	4	Full Thread	3	2	0.8	1.5	1.5 -	2.6	20
SVFSS-M5	M5	0.8		8	10	12	16	20	25		11	8.5	5	16 (L=25)	4	2.5	1	1.5	2.9 -	5.2	20
SVFSS-M6	M6	1			10	12	16	20	25		12.5	10	6	Full Thread	5	3	1.6	2	4.9 -	7.5	20
SVFSS-M8	M8	1.25				12	16	20	25	30	17	13	8	Full Thread	6	4	1.6	2	11 -1	7	10

- \*1: If the "L" value is not in parentheses, the screw is full thread.
- When purchasing less volume than one full bag, a separate handling fee is charged. For details, see the Sold Separately Service.

• Part Number Specification



1 Individual Sales

🥵 Cleanroom Wash & Packaging 🔐 Screw Length Adjustment 💶 Vibration Resistant





