

## Material/Finish



	SNMX-TBZ-ALK
Main Body	Steel Black Trivalent Chromate Treatment
Nylon Patch	Nylon 11
Strength Class	4.8 Equivalent

## Application

Screw return and fallout prevented Prevention of damage to screw heads Reliable tightening

• Part Number Specification





- Hexalobular socket\*1 truss machine screws with nylon patch.
- The friction of the nylon adhered to the thread suppresses the return rotation of the thread.
- Even if the tightening force is lost, the return rotation is suppressed, preventing the screws from falling off.
- The heat resistant temperature of the nylon patch is 120℃.
- Hexalobular socket shapes are designed to withstand high tightening torque compared to cross-recesses.
- Recesses are unlikely to be damaged due to tightening, allowing safe and secure tightening to be performed.
- \*1: The hexalobular shape is prescribed by JIS B 1015: 2008(ISO 10664: 2005)"Hexalobular internal driving feature for bolts and screws".

Unit: mm

Part Number 1	M (Coarse)			L 12					D <sub>1</sub>	L1	Hexalobular	Mass (g)	Qty per Pack
	Nominal of Thread	Pitch							וט	-	Socket No.	iviass (g)	Qty per rack
SNMX-M3-TBZ-ALK	M3	0.5	6	8	10				6.9	1.9	10	0.63 - 0.79	10
SNMX-M4-TBZ-ALK	M4	0.7	6	8	10	12	16	20	9.4	2.5	20	1.4 - 2.3	10
SNMX-M5-TBZ-ALK	M5	0.8			10	12	16	20	11.8	3.1	25	2.8 - 4.3	10
SNMX-M6-TBZ-ALK	M6	1			10	12	16		14	3.7	30	4.6 - 5.6	10

• When purchasing less volume than one full bag, a separate handling fee is charged. For details, see the Sold Separately Service.

## Related Products

**SKX** Hexalobular Wrench



**SKX-N** Hexalobular Wrench for **Extremely Limited Access** Spaces




**SKXB** Hexalobular Short Bit



**SRD** Magnet Screwdriver



1 Individual Sales Available / Add'l charge | Available / Add'l charge







Modification process for captive use Not Available

